



CAP. TONS	SPAN L	A	B	F	WHEEL BASE	WHEEL DIA.	NO. OF WHEELS	CRANE RAIL	BRIDGE SPEED	POWER SUPPLY	BRIDGE WEIGHT LBS.	MAX. WHEEL LOAD LBS.	GIRDER TYPE
7 1/2	20'-0"	9'-0"	9"	2'-3"	7'-6"	8"	4	40#	100 FPM VARIABLE	460/3/60	4700	9100	BEAM
	24'-0"			2'-6"							6000	9700	
	28'-0"			2'-7"							7000	10100	
	32'-0"			2'-7"							8300	10600	
	36'-0"			2'-9"							10500	11300	
7 1/2	40'-0"	9'-0"	9"	3'-0"	7'-6"	8"	4	40#	100 FPM VARIABLE	460/3/60	12600	12000	BEAM
	44'-0"			3'-0"							12500	12100	
	48'-0"			3'-1"							15300	12900	
	52'-0"			3'-3"							16400	13300	

NOTES:
 1. BRIDGE WEIGHTS ARE BASED ON A MAXIMUM TROLLEY WEIGHT OF 1500 LBS.

ACECO
 AMERICAN CRANE & EQUIPMENT CORPORATION
 DOUGLASSVILLE, PA. 19518 U.S.A.
 PHONE: 610-385-6061
 FAX: 610-385-3191

TOP RUNNING
 DUOBEM CRANE
 WITH FIXED AXLE WHEELS
 7 1/2 TON CAPACITY

PRODUCT INFORMATION
 DWG. NO: A-20418-1202
 DATE: 4/17/13

DWN. BY:
 CHK. BY:
 APP. BY: