



CAP. TONS	SPAN L	A	B	C	F	J MIN.	K	WHEEL DIA.	# OF WHEELS	W.B.	MAX. WHEEL LOAD LBS. (PER PAIR)	BRIDGE WEIGHT LBS.
5	20'-0"	9"	6 1/2"	7"	18"	17"	13"	7.5"	8	5'-3"	7400	3300
	30'-0"	9"	6 1/2"	9"	18"	17"	13"	7.5"	8	5'-3"	7800	5300
	40'-0"	9"	6 1/2"	12"	18"	17"	13"	7.5"	8	5'-3"	8300	7200
	50'-0"	11"	6 1/2"	18"	18"	17"	15"	7.5"	8	8'-3"	8800	9000
	60'-0"	11"	6 1/2"	19"	18"	17"	18"	9"	8	10'-6"	9200	10700

	TROLLEY MODEL	
LIFT	3111D-1423	3111D-2423
TROLLEY WEIGHT	23'-3"	33'-1"
D	860 LBS.	920 LBS.
E	8"	8"
H	1'-8"	1'-8"

HOISTING SPEED	16/4 FPM
BRIDGE SPEED	100/25 FPM
TROLLEY SPEED	67/15 FPM
POWER SUPPLY	460/3/60

- NOTES:
1. HOIST CLASSIFICATION: HMI H4 / FEM 3M
  2. LONGER LIFTS ARE AVAILABLE.
  3. SPEEDS SHOWN ARE STANDARD, OTHER SPEEDS ARE AVAILABLE.
  4. VARIABLE FREQUENCY DRIVES ARE AVAILABLE FOR BRIDGE AND TROLLEY.

**ACCECO**  
 AMERICAN CRANE  
 & EQUIPMENT CORPORATION  
 DOUGLASSVILLE, PA. 19518 U.S.A.  
 PHONE: 610-385-6061  
 FAX: 610-385-3191

UNDER RUNNING  
 SINGLE GIRDER CRANE  
 (WITH MODULAR HOIST)

5 TON CAPACITY

PRODUCT INFORMATION

DWG. NO: A-20418-401

DATE: 11/26/02 REVISION: 2