



CAP. TONS	SPAN L	A	B	C	F	J MIN.	K	WHEEL DIA.	# OF WHEELS	W.B.	MAX. WHEEL LOAD LBS. (PER PAIR)	BRIDGE WEIGHT LBS.
7 1/2	20'-0"	11"	6 1/2"	6'	18"	17"	14'	9"	8	5'-3"	10000	4000
	30'-0"	11"	6 1/2"	9"	18"	17"	14"	9'	8	5'-3"	10600	6400
	40'-0"	11"	6 1/2"	11"	18"	17"	14"	9"	8	5'-3"	11100	8400
60'-0"	50'-0"	11"	6 1/2"	18'	18"	17"	16"	9"	8	8'-3"	11700	10500
	60'-0"	14"	6 1/2"	20'	18"	17"	20"	9"	8	10'-6"	12100	12500

	TROLLEY MODEL	
LIFT	3121B-1423	3121B-2423
TROLLEY WEIGHT	21'-3"	29'-2"
D	1'-4"	1'-4"
E	11"	1'-5"
H	2'-3 1/2"	2'-3 1/2"

HOISTING SPEED	16/4 FPM
BRIDGE SPEED	100/25 FPM
TROLLEY SPEED	67/17 FPM
POWER SUPPLY	460/3/60

- NOTES:
1. HOIST CLASSIFICATION: HMI H4 / FEM 3M
 2. LONGER LIFTS ARE AVAILABLE.
 3. SPEEDS SHOWN ARE STANDARD. OTHER SPEEDS ARE AVAILABLE.
 4. VARIABLE FREQUENCY DRIVES ARE AVAILABLE FOR BRIDGE AND TROLLEY.

ACECO 

AMERICAN CRANE & EQUIPMENT CORPORATION
 DOUGLASSVILLE, PA. 19518 U.S.A.
 PHONE: 610-385-6061
 FAX: 610-385-3191

UNDER RUNNING SINGLE GIRDER CRANE (WITH MODULAR HOIST)

7 1/2 TON CAPACITY

PRODUCT INFORMATION

DWG. NO: **A-20418-402**

DATE: 11/26/02 REVISION: 1