



CAP. TONS	SPAN L	A	F	J	W.B.	BRIDGE WEIGHT LBS.	MAX. WHEEL LOAD LBS.	GIRDER SIZE	Wheel Dia.
20	20'-0"	8'-11"	2'-2"	1'-4"	6'-6"	8500	23500	W16x89	12.4"
	24'-0"	8'-11"	2'-3"	1'-4"	6'-6"	10150	24150	W18x97	
	28'-0"	8'-11"	2'-4"	1'-4"	6'-6"	11800	24800	W21x111	
	32'-0"	9'-0"	2'-5"	1'-5"	6'-6"	13450	25450	W21x132	15.75"
	36'-0"	9'-0"	2'-6"	1'-5"	6'-6"	15100	26100	W24x76 w/C15.33.9	
	40'-0"	9'-0"	2'-7"	1'-5"	6'-6"	16750	26750	W27x94 w/C15x33.9	
	44'-0"	9'-0"	2'-8"	1'-5"	6'-6"	18400	27400	W27x102 w/C15x33.9	
	48'-0"	10'-8"	2'-9"	13"	8'-6"	20050	28050	W30x108 w/C18x42.7	
	52'-0"	10'-8"	2'-10"	13"	8'-6"	21700	28700	W30x124 w/C18x42.7	

	TROLLEY MODEL **		
	3131B-1626	3131B-2626	3131B-3626 *
LIFT	17'-4"	23'-11"	32'-9"
TROLLEY WGT	3900 LBS.	4000 LBS.	4500 LBS.

\* Longer Wheel Base required  
 \*\* Longer Lift available

HOISTING SPEED	11/4 FPM
BRIDGE SPEED	80/20 FPM
TROLLEY SPEED	83/20 FPM
RUNWAY RAIL	60# ASCE
POWER SUPPLY	460-3-60

NOTES:

1. HOIST CLASSIFICATION: HMI H4 / FEM 3M
2. LONGER LIFTS ARE AVAILABLE.
3. SPEEDS SHOWN ARE STANDARD, OTHER SPEEDS ARE AVAILABLE.
4. VARIABLE FREQUENCY DRIVES ARE AVAILABLE FOR BRIDGE AND TROLLEY.



AMERICAN CRANE  
 & EQUIPMENT CORPORATION  
 DOUGLASSVILLE, PA. 19518 U.S.A.  
 PHONE: 610-385-6061  
 FAX: 610-385-3191

TOP RUNNING  
 DOUBLE GIRDER CRANE

20 TON CAPACITY

PRODUCT INFORMATION

DWG. NO:  
 A-20418-205

DATE: 10/29/02 REVISION:

DWN. BY:

CHK. BY:

APP. BY: